

OPTIMAL EASYFLOOR B-FREE is a 150 micron textured white PVC laminated with a removable dark grey acrylic adhesive. Slip resistance certified film for Floor Graphics advertising- not any additional laminating film required. The product is for short to medium term indoor applications. Expected lifetime is up to 2 months because of the variation in durability of the ink. The product is suitable for printing by Latex, UV & most solvent based inks.

Product is suitable for

- Short to Mid Term Application
- Indoor Use
- POS Signage/ General Signage
- Floor Graphics - Applicable to: floor tiles, pvc flooring, concrete/stone floor, wooden/laminated floors carpets (low pile carpets - but should be tested on small area to prove performance)

Product Benefits are

- Clean remove product, however minimal residue can transfer on to surface
- For ease of application OPTIMAL EASYFLOOR B-FREE is supplied with an 'air free' structured release liner
- Slip Resistant
- Fire Resistant
- No lamination required
- Good scratch resistance

Standard Sizes

Width: 1370 mm

Length: 50 m

Product Features and Performance Data

Face Material	Textured White Monomeric PVC	150 $\mu\text{m} \pm 10$
Adhesive	Acrylic water based PSA moderate tack	26 $\mu\text{m} \pm 2$
Liner	Structured air release, 1 side siliconized	135 $\mu\text{m} \pm 10$
Application temperature		10 - 40 °C
Slip Test	DIN 51130: 2014	R9
Fire Test	EN13501-1:2007 +A1 2009	C-s1 d0

This information is given as a guideline and due to the wide variation in surface to which this product may be applied the end user MUST carry out suitable testing to satisfy themselves as to satisfactory performance. Due to the wide variation in potential surfaces supplier cannot accept any responsibility for the adhesive performance in the event of adhesion failure.